

ATF D III

DESCRIPTION :

Semi-synthetic oil with a very high viscosity index for most of the automatic transmission. The improved fluidity at low temperatures ensures optimum performance in all conditions. Its exceptional frictional characteristics provide smooth switching and driving comfort.

APPLICATIONS :

This oil can be used in automatic transmissions, torque converters, power steering and hydraulic circuits, for which the manufacturers prescribe a product, which meets the GENERAL MOTORS ATF TYPE DEXRON III or DEXRON II E and FORD MERCON-requirements.

SPECIFICATION LEVEL :

MB	236.1, 236.5, 236.6, 236.7	ZF	TE-ML 02F, 03D, 04D, 09, 11B, 14A, 17C
MAN	339 F	HAGGLUNDS-	HF-0
GM	DEXRON III G (GM 6417M)	DENISON	
FORD	MERCON	VOITH	55.6335 (G607)
	WSA-M2C-195A (Service Fill)	ALLISON	C4
CAT	TO-2		

TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
Colour			red
Density at 15°C	D 4052	kg / m ³	862
Viscosity at 40°C	D 445	cSt	34,3
Viscosity at 100°C	D 445	cSt	7,7
Viscosity -40°C	D 2893	mPa.s	18400
Viscosity index	D 2270		205
Pour point	D 6892	°C	-45
Flash point COC	D 92	°C	196

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.